

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY OFFICE OF RADIATION PROGRAMS-LAS VEGAS FACILITY



P.O. BOX 18416, LAS-VEGAS, NEVADA 89114-5027 9 702/798-2100 (FTS 545-2100)

JAN 2 5 1983

Marc E. Nelson Environmental Scientist U.S. Department of the Interior Geological Survey Box 26124 Albuquerque, New Mexico 87125

Confidential Claim Retracted

RECEIVED

JAN 28 1983

PHEBLO OF LAGUNA GOVERNOR'S OFFICE

Dear Mr. Melson:

Attached is a tabulation of our findings resulting from follow-up surveys of radiation anomalies described by our gamma scanner work at the Pueblo of Laguna.

You may use our recently approved standards for uranium mill tailings as a comparison for the values I have presented. Summarily, the standard says that cleanup of buildings should be effected to reduce radon daughter working levels to 0.02, with a maximum limit of 0.03. Gamma exposure rates should be reduced to less than 20 μ R/hr above background. Dispersed tailings should be cleaned up to less than 5 pCi/g averaged over the top 15 centimeters of soil, and to 15 pCi/g averaged over any 15 centimeters of soil below this. Note that these standards are specific for the cleanup and control of inactive uranium mill tailings and do not make prescriptions for mine wastes or natural outcroppings of minerals which may exceed 5 pCi/g.

Sincerely yours,

Wayne A. Bliss, Director

Las Vegas Facility

Office of Radiation Programs

ayne a Blis

Attachment (as stated)

cc: w/attachment

- -> H. Early, Pueblo of Laguna

J. Silhanek, ANR-460

H. May, Region VI

C. Spotts, Region VI

A. Topp, NMEID

XC: Ron J. Solimon

9403972